

STARLIGHT INTEGRATED LED SPOTLIGHT

DESCRIPTION

The Starlight recessed spot is a premium design recessed spotlight featuring an integrated LED module of 6 watts with a lifespan of 50,000 hours and can replace halogen lamps up to 65 watts, achieving savings of over 90% in energy costs. As there is a narrow rim, there is a perfect integration with e.g. system-, stucco- and plaster ceilings. Due to the fixture's optimized lens design and depth, the Starlight has a UGR value of <15, which according to the EN 12464: 2011 is practically suitable for every application. Thanks to a high color rendering of CRI90 / RA90< where colors come alive, this spotlight is also applicable for the most luxurious applications.

Thanks to the IP54 rating, the fixture is splash proof and dust proof, allowing it to be used in a wide range of environments including those which are humid and dusty. Altogether, this fixture is suitable for applications with very high standards and will guarantee a pleasant light experience.



APPLICATIONS



Office



Hotel



Restaurant



Retail



Housing

OPTIONAL

- 5 year warranty

SPECIFICATIONS

EAN	Item description	Power (W)	Lumen	Efficacy (lm/W)	Input current	CCT (K)	CRI	Equivalent	Lifespan L80 at 25°C
8719157001953	LED Spotlight Starlight Integrated COB Sand white IP54 6W CRI90 2700K Cutout size Ø80mm - including dimmable driver	6	400	70	0.04A	2700	>90	65W	50,000
8719157002332	LED Spotlight Starlight Integrated COB Aluminum IP54 6W CRI90 2700K Cutout size Ø80mm - including dimmable driver	6	400	70	0.04A	2700	>90	65W	50,000

Luminous flux tolerance: +/- 10% Power consumption tolerance: +/- 10%

PACKAGING INFORMATION

Item	Item description	Box 1 Item		Units per masterbox	Masterbox	
		Dimensions (mm) (HxWxD)	Weight (kg)		Dimensions (mm) (HxWxD)	Weight (kg)
8719157001953	LED Spotlight Starlight Integrated COB Sand white IP54 6W CRI90 2700K Cutout size Ø80mm - including dimmable driver	120x140x140	0.300	36	385x440x580	10.8
8719157002332	LED Spotlight Starlight Integrated COB Aluminum IP54 6W CRI90 2700K Cutout size Ø80mm - including dimmable driver	120x140x140	0.300	36	385x440x580	10.8

TECHNICAL SPECIFICATIONS

Technical specifications

UGR	<15
Dimmable	Yes
Beam angle (°)	36°
IP	IP54
IK	IK02
Protection class	II
Driver included (Yes/No)	Yes
Glow wire test	650°C

Electrical supply

Frequency (Hz)	50-60
Voltage (V)	220-240
AC/DC	AC
Power factor	>0.9

Application

Operating temperature	-20 to +45°C
-----------------------	--------------

Physical characteristics

Diameter Ø (mm)	85
Cutout size Ø (mm)	80
Installation depth (mm)	90
Tilting	No
Montage	Recessed
Suitable for ceiling thickness (mm)	2 - 20


Mechanical properties

Housing material	Aluminum
Color (Housing)	Sand white, Aluminum
Optic	Polycarbonate

Certifications

Driver certifications	CE
Fixture certifications	CE
Test reports	LM80-08


DIMENSIONAL DRAWINGS





PHOTOMETRIC SPECIFICATIONS

Spotlight Starlight COB IP54 6W 10V 927

Luminous emittance 1 / Polar LDC



Luminous emittance 1 / Cone diagram



NOXION

© 2017 Noxion B.V. - All rights reserved. Noxion retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors.

Version: May 2018